



CLARK EUROPE GMBH
 Neckarstrasse 37
 D-45478 Mülheim an der Ruhr/Germany
 Tel.: +49 208 377336-0
 Fax: +49 208 377336-36
 www.clarkmheu.com
 info-europe@clarkmheu.com

| 1. Characteristics | | | | |
|---------------------|--------------------|---|---------------------------------------|-------------------------------|
| 1.1 | Manufacturer | | | CLARK |
| 1.2 | Model | denomination of model in production | | C OP 20 1.150 x 540 |
| 1.3 | Capacity | Q | nominal capacity | Kg 2.000 |
| 1.4 | Load center | c | distance to load center | mm 600 |
| 1.5 | Power | E =Elektric | | E |
| 1.6 | Control | T = Tiller / A = Pedestrian | | T / P |
| 1.7 | Service Brake | M (mechanic) I (hydraulic) E (electric) | | E |
| 1.8 | Parking Brake | (.) pedal (..) parking (...) tiller arm | | (.) (..) |
| 2. Wheels | | | | |
| 2.1 | Wheels type | plt = polyurethane g= rubber | | plt |
| 2.2 | Wheels | | quantity (x =traction) front/rear | Nr. 1x + 2/4 |
| | | | front wheels size | mm 245 / 150 |
| | | | rear wheels size | mm 85 |
| 3. Dimensions | | | | |
| 3.1 | Lifting | h2 | lifting | mm 120 |
| 3.2 | Max. dimensions | L2 | length overall including forks face | mm 1.240 |
| | | B | width | mm 800 |
| 3.3 | Wheel base | Y | wheel base | mm 2.010 |
| 3.4 | Wheel base | at wheels center front/rear | | mm 550 / 360 |
| 3.5 | Clearance | chassis | | mm 55 |
| | | cuttriggers | | mm 25 |
| 3.6 | Turning radius | Wa | radius | mm / |
| 3.7 | Stacking aisle | Ast3 | with pallet (800x1.200 / 1.000x1.200) | mm / |
| 4. Performances | | | | |
| 4.1 | Speeds | traction with/without load | | km/h 9.5 / 10.5 |
| | | lifting with/without load | | m/sec 0.04 / 0.05 |
| | | lowering with/without load | | m/sec 0.26 / 0.06 |
| 4.2 | Gradeability | nominal 30' with/without load | | % / |
| 4.3 | Max. gradeability | for 5' with/without load | | % 10 / 18 |
| 4.4 | acceleration time | from 0 to 10 m with/without load | | sec / |
| 5. Weight | | | | |
| 5.1 | Total weight | battery included | | Kg. 950 |
| 5.2 | Axle loading | with load front/rear | | Kg. / |
| | | without load front/rear | | Kg. / |
| 6. Battery - Motors | | | | |
| 6.1 | Battery | volatge | | V 24 |
| | | capacity | | Ah 300 |
| | | min. weight | | Kg. 285 |
| 6.2 | Electrical | traction (S2 - 60') | | KW 2.6 |
| | | lifting (S3 - 20%) | | KW 2 |
| 6.3 | Hydraulic pressure | max. pressure | | bar 120 |
| 6.4 | Noise level | operators place | | dB < 70 |

CLARK EUROPE GMBH has the right to change datas and informations without prior announcement. Informations and datas anre not binding.

